A2422 Portable Carbon Monoxide Detectorinstruction manual



Technical Support

The carbon monoxide detector alarm can be connected to any switch and heater device that matches the model shown below, and the device can be turned off through 433mhz control. If you have any questions, please feel free to contact us: **sunster202@163.com**

1, Product description :

2. Power on/off: When the device is powered on, press the [Power button] to turn it on/off;

3. Basic settings: After turning on the device, long press the [Power button] to enter the basic settings mode; view the settings:

F00: Current time F01: Temperature compensation (±9℃); F02 : ℉/℃ switch;

F03: Remote control learning (only learn the shutdown button) F04: CO Alarm threshold setting;

F05: Bluetooth Mesh Network settings;

1. Current time setting: Press the [Set] key to switch; press the [Add]/[Subtract] key to adjust the parameters. Set; press [Set] again to save;

2. Temperature compensation: The operation method is the same as <Current time setting>; the compensation range is (-9℃~9℃)

3. ℉/℃ switch: The operation method is the same as <Current time setting>; after switching, press the [Power button] to return to operation. In the line interface, the temperature display unit automatically

switches and updates;

4. Remote control learning: In the basic settings interface, press the [Set] key to set; press the [Add]/ [Subtract] key to Key] to switch the learning type;

RF:00 Indicates the remote control to be added;

RF:24 Indicates sending twenty four Byte type remote control; RF:32 Indicates sending 32 Byte type remote control;

5. Learning method: Refer to the QR code

6. CO Alarm threshold setting: In basic setting mode, adjust to F04: CO Alarm threshold setting; press [Set Press the [+] key/[-] key to set (threshold The value range is 0～500PPM) default standard value 300PPM;

7. Bluetooth Mesh Network settings: (Note: The settings here have been A2409 For example, the actual connection method is different from the display Icon, please check the model of the switch used with it) After the connection is successful, the switch and the controller will automatically update the synchronization time: A2422-CO The detector detects more than 300PPM The controller is every (interval 10 seconds) alarm, Continue to exceed 500PPM(60 The controller

controls the switch to shut down, and the switch continues to flash as an alarm. E11 error code。



A2422 Návod k použití přenosného detektoru oxidu uhelnatého

1 , Popis výrobku :

2. Zapnutí/vypnutí: Když je zařízení zapnuté, stisknutím [tlačítko napájení] jej zapněte/vypněte;

3. Základní nastavení: Po zapnutí zařízení dlouze stiskněte [tlačítko Napájení] pro vstup do režimu základního nastavení; zobrazit nastavení:

F00: Aktuální čas F01: Teplotní kompenzace (± 9 ℃);

F02 : spínač ℉/℃;

F03: Učení dálkového ovládání (naučte se pouze tlačítko

vypnutí) F04: CO Nastavení prahu alarmu;
F05: Bluetooth Pletivo Nastavení sítě;
1. Nastavení aktuálního času: Pro přepnutí stiskněte tlačítko [Set]; stiskněte tlačítko [Add]/[Subtract] pro úpravu parametrů. Soubor; znovu stiskněte [Set] pro uložení;
2. Teplotní kompenzace: Způsob provozu je stejný jako <Nastavení aktuálního času>; rozsah kompenzace je (-9℃~9℃)
3. Přepínač ℉ / ℃ : Způsob provozu je stejný jako <Nastavení aktuálního času>; po přepnutí stiskněte [tlačítko napájení] pro návrat do provozu. V rozhraní linky se jednotka zobrazení teploty automaticky přepíná a aktualizuje;
4. Učení dálkového ovládání: V rozhraní základních nastavení stiskněte tlačítko [Set] pro nastavení; stiskněte tlačítko [Přidat]/ [Odečíst] Key] pro přepnutí typu učení;
RF:00 Označuje dálkové ovládání, které má být přidáno;
RF:24 Označuje odeslání dvacet čtyři Dálkové ovládání typu byte; RF:32 Označuje odeslání 32 Dálkové ovládání typu byte;
5. Metoda učení: Viz QR kód

6. CO Nastavení prahu alarmu: V režimu základního nastavení nastavte na F04: CO Nastavení prahu alarmu; stiskn ě te [Nastavit Stiskn ě te klávesu [+]/[-] pro nastavení (prah Rozsah hodnot je 0～500PPM) výchozí standardní hodnota 300 ppm;

7.Bluetooth Pletivo Nastavení sít ě : (Poznámka: Nastavení zde byla A2409 Například skutečný způsob připojení se liší od zobrazení Ikona, zkontrolujte prosím model přepínače, který s ním používáte) Po úsp ě šném připojení přepínač a ovladač automaticky aktualizují čas synchronizace : A2422-CO Detektor detekuje více než 300 ppm Ovladač je každý (interval 10 sekund) alarm, Pokračujte v překračování 500 ppm (60 Ovladač ovládá spínač, aby se vypnul, a spínač nadále bliká jako alarm. E11 chybový kód